Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	johnson near platform	US-PGPUB; USPAT	OR	OFF	2005/08/24 13:15
L2	0	(stewart near platform).ti.	US-PGPUB; USPAT	OR	OFF	2005/08/24 13:15
L3	39	(parallel near kinematic) same platform	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 13:44
L4	157	(parallel near kinematic)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 13:49
L5	73	L4 and @ad<"20020305"	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 13:49
L6	0	(parallel near kinematic)	IBM_TDB	OR	OFF	2005/08/24 13:49
L7	0	stewart near platform	IBM_TDB	OR	OFF	2005/08/24 13:50
S17	21	"6132108".pn. "6077302".pn. "6023574".pn. "6224249".pn. "6081654".pn. "6044210".pn. "5920491".pn. "5901072".pn. "5623642".pn. "5297057".pn. "5253189".pn. "5249151".pn. "6161080".pn. "6063126".pn. "5956500".pn. "5913955".pn. "5654900".pn. "5163015".pn. "20010032065" "20010020386" "6178540".pn.	US-PGPUB; USPAT	OR	OFF	2005/08/22 10:55
S18	246	703/8.ccls. and @ad<"20020305"	US-PGPUB; USPAT	OR	OFF	2005/08/22 11:28
S19	1478	spring adj design	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 11:28
S20	1177	S19 and @ad<"20020305"	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 12:01
S21	265	S20 and torque	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 12:59
S22	1083	measure near7 force$1 and measure near7 torque$1	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 13:00

S23	828	S22 and @ad<"20020305"	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 13:10
S24	124	S23 and model	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 13:03
S25	18	S24 and suspension	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 13:03
S26	334	S23 and test$3	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 13:58
S27	2	"20030111309"	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 17:53
S28	153	stewart adj platform	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 14:18
S29	105	S28 and @ad<"20020305"	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 15:05
S30	41706	marc	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 15:05
S31	81115	adams	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 15:05
S32	52	(stewart adj platform) and (universal adj joint)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 17:54
S33	35	S32 and @ad<"20020305"	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 18:21
S34	2	"5,656,905".pn.	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 13:43

S35	2	"5,797,191".pn.	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/22 18:53
S37	1770	spring and (side adj force)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 10:29
S38	15	S37 and variable near pitch	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 10:30
S39	2	spring and (variable near pitch) and (transverse near load$3)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 10:31
S40	3	spring and (variable near pitch) and (lateral near load$3)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 10:39
S41	13	spring and (variable near pitch) and (side near load$3)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 10:52
S42	1721	spring and (variable near pitch)	US-PGPUB; USPAT; EPO; DERWENT	OR	OFF	2005/08/24 10:52
S43	1498	spring and (variable near pitch)	US-PGPUB; USPAT	OR	OFF	2005/08/24 10:52
S44	1290	S43 and @ad<"20020305"	US-PGPUB; USPAT	OR	OFF	2005/08/24 10:52
S45	16	S44 and spring.ti.	US-PGPUB; USPAT	OR	OFF	2005/08/24 10:53
S46	7	S44 and side near load	US-PGPUB; USPAT	OR	OFF	2005/08/24 13:07

Google Scholar ○ BETA

| spring "parallel kinematic" | Search |

Scholar

Results **1 - 10** of about **49** for <u>spring</u> **"parallel kinematic"**. (0.07 seconds)

The pride prototype: control layout of a parallel robot for assembly tasks.

LE Bruzzone, RM Molfino, M Zoppi, G Zurlo - 22 nd IASTED International Conference on Modelling, ..., 2003 - dimec.unige.it

... The end-effector acts as a three-dimensional **spring**- damper system, which ... approach to the design and selection of joints for **parallel kinematic** structures with ...

<u>Cited by 2</u> - <u>View as HTML</u> - <u>Web Search</u> - <u>csa.com</u>

Mechatronic design of a parallel robot for high-speed, impedance-controlled manipulation

LE Bruzzone, RM Molfino, M Zoppi - Proc. of the 11th Mediterranean Conference on Control and ..., 2003 - dimec.unige.it

... end-effector behaves like a three-dimensional **spring**- damper system ... Kinematics, 3rd Chemnitz Parallel Kinematics Seminar, 2002 **Parallel Kinematic** Machines Intl ...

<u>Cited by 1</u> - <u>View as HTML</u> - <u>Web Search</u> - <u>dimec.unige.it</u> - <u>med.ee.nd.edu</u>

Kinematic and dynamic synthesis of a parallel kinematic high speed drilling machine

R Katz, Z Li - International Journal of Machine Tools and Manufacture, 2004 - csa.com

... The paper is focused on the kinematic and dynamic synthesis of this **parallel kinematic** machine (PKM ... at reducing the input power of the PKM using a **spring** element ...

<u>Web Search</u> - <u>csa.com</u>

DYNAMIC SYSTEM IDENTIFICATION OF PARALLEL KINEMATIC MACHINES By Michael R. Heger and Gloria J. Wiens ...

MR Heger - cimar.me.ufl.edu

1 DYNAMIC SYSTEM IDENTIFICATION OF **PARALLEL KINEMATIC** MACHINES By ... As of to date, there has been limited research in the area of **parallel kinematic** machines. ...

<u>View as HTML</u> - <u>Web Search</u> - <u>me.ufl.edu</u> - <u>cimar.mae.ufl.edu</u>

Modeling and model based performance prediction for parallel kinematic manipulators

JG Persson, K Andersson - md.kth.se

... 7. Conical-helical involute gear, axially **spring** preloaded for anti-backlash. ... Especially with the complex kinematic structure of **parallel kinematic** robots, a ...

<u>View as HTML</u> - <u>Web Search</u>

Connection method for dynamic modelling and simulation of parallel kinematic mechanism (PKM) machines ...

Q Huang, H Hadeby, G Sohlenius - International Journal of Advanced Manufacturing Technology, 2002 - springerlink.com

... A **parallel kinematic** mechanism (PKM) machine, which is also called a parallel robot as ... can be generalised as one of three basic types: **spring**, damper, or mass. ...

<u>Web Search</u> - <u>csa.com</u>

Parallel kinematic machine design with kinetostatic model

D Zhang, CM Gosselin - Robotica, 2002 - journals.cambridge.org

Parallel kinematic machine design with kinetostatic model ... if it is associated with a virtual joint, where k i is the stiffness of the virtual **spring** located at ...

<u>Web Search</u> - <u>journals.cambridge.org</u> - <u>portal.acm.org</u> - <u>csa.com</u> - <u>all 7 versions »</u>

Kinematic and dynamic analyses of a micro parallel-link mechanism

SS Kwak, JI Mou, SRS Huang - Microsystem Technologies, 2004 - springerlink.com

... The concept is based on rack-and-pinion actuation of **parallel kinematic** struts with ... The mo- vable comb can be supported by a flexible **spring**, and large motions ...

<u>Web Search</u> - <u>portal.acm.org</u>

Robust adaptive control of a HexaSlide type parallel manipulator
JP Kim, SG Kim, J Ryu - Asia-Pacific Conference on Control and Measurement, 4 th, ..., 2000 - ijcas.com
... proposed control law is developed based on a simplified sec- ond order system dynamic
equation in joint space with uncertain mass, damper, **spring**, and Coulomb ...
View as HTML - Web Search - ijcas.com - dyconlab.kjist.ac.kr - csa.com

Kinetostatic Modeling of N-DOF Parallel Mechanisms With a Passive Constraining Leg and Prismatic ...
D Zhang, CM Gosselin - Journal of Mechanical Design, 2001 - link.aip.org
... joint, where is the stiffness of the virtual **spring** located at ... Machine Tool Family,"
in Proceedings of Year 2000 **Parallel Kinematic** Machines International ...
Cited by 3 - Web Search - csa.com

Gooooogle ▶
Result Page: **1** 2 3 4 5   **Next**

spring "parallel kinematic"	Search

Google Home - About Google - About Google Scholar

CiteSeer Find: |spring   : Documents | Citations |

Searching for **PHRASE spring parallel kinematic**.
Restrict to: <u>Header</u> <u>Title</u> Order by: <u>Expected citations</u> <u>Hubs</u> <u>Usage</u> <u>Date</u> Try: <u>Google (CiteSeer)</u>
<u>Google (Web)</u> <u>Yahoo!</u> <u>MSN</u> <u>CSB</u> <u>DBLP</u>
No documents match Boolean query. Trying non-Boolean relevance query.
500 documents found. **Order: relevance to query.**

<u>Global Asymptotic Stabilization of a Spinning Top With Torque.. - Wan (1996)</u> (Correct)
Isidori, Nonlinear Control Systems, 2nd edition, **Springer**-Verlag: Heidelberg, 1989. 10. H. K. Khalil,
are inertially-fixed horizontal forces and the **kinematic** formulation was based on the 2-1-3 Euler
and takes advantage of a new formulation for the **kinematics** of the rotational motion developed in [14]
www.ae.gatech.edu/people/tsiotras/Papers/dc96.ps.gz

<u>Formulating 3D Contact Dynamics Problems - Mihai Anitescu</u> (Correct)
do not exhibit certain peculiarities (such as **parallel** edge-on-edge contact or excessive mutual
constraints the contact points as well as the **kinematic** data needed to set up the dynamics equations
Section 4 is concerned with determining the **kinematic** data of the contact constraint Section 5
www.math.pitt.edu/~anitescu/PUBLICATIONS/contacte3.ps.Z

<u>H1 Collaboration - Ti On</u> (Correct)
in the H1 laboratory frame. Abstract: 558 **Parallel** sessions: 5,7 Plenary sessions: 7,9 1
(stat.Sigma35 syst.pb is measured in the **kinematic** range 2 !Q 2 100 GeV 2 0:05 !y !
allowing a more accurate measurement over a wider **kinematic** range. 2 Event Selection The data were
www-h1.desy.de/h1/www/psfiles/confpap/vancouver98/abstracts/558-thompson-paper.ps

<u>Dis At Hera - Mario Martinez</u> (Correct)
Carlo generated events and are given for the **kinematic** region Q 2 100 GeV 2 The measured
sections for the reaction ep !e jet X in the **kinematic** region defined by Q 2 125 GeV 2 have been
are described by the predictions in the entire **kinematic** region studied. Figure 4: Measured differential
zedy00.desy.de/conferences98/wmario.ps.gz

<u>Limit Cycle Control and its Application to the Animation.. - Laszlo, Panne, Fiume (1996)</u> (Correct) (15 citations)
ground is modelled using a penalty method. Stiff **springs** and dampers exert forces on a set of four points
to model because of their inherent instability. **Kinematic** animation techniques can freely ignore such
which are based on empirical data or on **kinematic** relationships. The work of [3] uses a mixed
www.dgp.utoronto.ca/people/van/limcycle.ps.gz

<u>Bruce Straub - Columbia University</u> (Correct)
is mediated by the exchange of a W boson. The **kinematics** of DIS reactions are described by two
it was taken after the determination of the **kinematic** regions where excess event rates were observed
cross sections are described in section 2. The **kinematics** and reconstruction methods used for DIS at HERA
www-zeus.desy.de/~ukatz/ZEUS_PUBLIC/hqex/procd/proc_bs_lp97.ps.gz

<u>Dynamic Analysis of Human Walking - Faure, Debunne, Cani-Gascuel, Multon (1997)</u> (Correct) (3 citations)
phase, swing phase, double stand, etc. Children **parallel** state machines describe the sub-cycles local to
much skill since biomechanics analyses the **kinematics** of captured motion while simulators take the
walking gaits. We first convert a priori **kinematic** knowledge on human walking described by
w3imagis.imag.fr/Publications/faure/HumanGaitAnalysis.ps.gz

<u>A Topology Based Approach For Exploiting Sparsity In Multibody.. - Dan Negrut (1997)</u> (Correct) (2 citations)
II: Stiff and Differential-Algebraic Problems, **Springer**-Verlag, Berlin [5] Harwell Subroutine Library,
inertia matrix technique and to the degree of **parallel**ism attainable with the new algorithm. 1
Reference frames for each successive body in the **kinematic** chain are defined in the same way as those for
ftp.cs.uiowa.edu/pub/comp_math_rep/report-94.ps.Z

<u>Feedback Stabilization of Nonholonomic Systems in Presence of .. - Lizarralde, Wen (1996)</u> (Correct)
1994. 10] A. Isidori, Nonlinear Control Systems. **Springer**-Verlag, 1989. 11] J. Laumond, Controllability
car orientation. The nominal control result for **parallel** parking is shown in Figure 3. The initial
nonlinear systems with no drift, which include **kinematic** models of nonholonomic systems, there is a
brahma.coep.ufrj.br/~fernando/papers/icra96.ps

<u>A Dynamical Model of Context Dependencies for the.. - Coenen, Sejnowski (1996)</u> (Correct) (1 citation)

and head translation)We first describe a **kinematic** model of the VOR which relies solely on sensory
of the VOR which can be described by the **kinematics** of the reflex, i.e. eye position, eye vergence
head translation. 2 The Vestibulo-Ocular Reflex: **Kinematic** Model a Top View Head Semicircular Canals and
ftp.cnl.salk.edu/pub/olivier/nips95.ps.Z

Motion Abstraction and Mapping with Spatial Constraints - Rama Bindiganavale (1998)   (Correct)   (14 citations)
horizontal step position may be input to inverse **kinematics** procedures to keep the body from floating or
optimization techniques [20, 24] to solve for the **kinematic** constraints imposed by the data itself. During
sensors lie on the body. To generate the motions, **kinematic** constraints are established between the newly
ftp.cis.upenn.edu/pub/graphics/rama/papers/mabstract.ps.gz

The Dynamic Servers Problem - Charikar, Halperin, Motwani (1998)   (Correct)   (3 citations)
and the problem of dynamic maintenance of **kinematic** structures for applications in molecular
structures and algorithms for the maintainence of **kinematic** structures, as described by Halperin, Latombe,
in 3-dimensional space and hinged together in a **kinematic** structure. We model these objects as a graph
theory.stanford.edu/people/rajeev/postscripts/servers.ps.gz

Crystal Barrel Collaboration A. Abele - Adomeit Amsler   (Correct)
the data are subjected to a series of **kinematic** fits. In a first step we impose energy and
are kept. This sample is then submitted to a 6C **kinematic** fit to the hypothesis pp!0 0 2fl and
pp!0 0 2fl and finally to a 7C **kinematic** fit to the hypothesis pp!0 0 j.
www.phys.cmu.edu/cb/papers/Eta_pi0_pi0_exotic.ps.gz

Steering Three-Input Chained Form Nonholonomic Systems.. - Bushnell, Tilbury.. (1993)   (Correct)   (2 citations)
1992. 3] A. Isidori. Nonlinear Control Systems. **Springer**Verlag, 2nd edition, 1989. 4] R. M. Murray and
i 1)o 1 =j 1 (7) Figure 2: Trace of **Parallel** Parking Trajectory -2 0 2 4 6 8 -1.0 -0.5 0.0
of a nonholonomic system is introduced. The **kinematic** equations are derived and represented as a
www-personal.engin.umich.edu/~tilbury/me662/caen/papers/ecc93.ps

Statically Stable Legged Locomotion with Leg Redundancy - Prattichizzo, Bicchi..   (Correct)
trajectories are generated by inverting the **kinematics** of the legs. If the walking robot posses more
planner and, by means of an optimizing inverse **kinematics** algorithm, generates related joint
exactly, x(t) f (q(t)being f (q) the direct **kinematic** relationship of the redundant robot whose
131.114.28.35/pub/papers/leg-iasted.ps.Z

Autonomous Maneuvers of a Nonholonomic Vehicle - Paromtchik, Garnier, Laugier (1997)   (Correct)
autonomously perform lane following/changing and **parallel** parking maneuvers. Lane following/changing
their autonomous abilities are being developed. A **kinematic** model of such a vehicle with front wheel
between the wheels and the ground. This purely **kinematic** f q x y Figure 1. **Kinematic** model of a vehicle
ftp.inrialpes.fr/pub/INRIA/projets/SHARP/publications/paromtchik:etal:iser:97.ps.gz

A Keck Hires Investigation Of The Metal Abundances And.. - Systems Toward   (Correct)
on QSO Absorption Lines, ed. G. Meylan, Berlin:**Springer**-Verlag)Vogt, S. S. 1992, in ESO Conf. and
Hires Investigation Of The Metal Abundances And **Kinematics** Of Three Damped Lyff Systems Toward
the two damped systems have vastly different **kinematic** characteristics. The z =1:920 system spans
preprints.cern.ch/archive/electronic/astro-ph/9605/9605021.ps.gz

Resolved Photon and Rapidity Gap in Jet Events - Hung Jung   (Correct)
of present and future particle colliders opens a **kinematic** regime, where the observation of jet events
by a logarithmic factor ln(s=4m 2 e)In the **kinematic** regime of our interest (p s ?300 GeV)this
pomeron is applicable. Notice that this **kinematic** regime differs from the previous gap event
preprints.cern.ch/archive/electronic/hep-ph/9508/9508361.ps.gz

Interactive Solid Animation Using Linearized Displacement.. - Faure (1998)   (Correct)   (6 citations)
time step. This perturbation acts much like damped **springs** applied to each constraint. This method has also
applications to animation such as inverse **kinematics**, dynamics, along with first results in
linearized geometric equation by writing it as a **kinematic** equation. Then we turn the non-square **kinematic**
www.cg.tuwien.ac.at/~francois/Public/Work/papers/interactiveDyna.ps.gz

Measurement And Qcd-Analysis Of The Proton Structure Function - At Hera   (Correct)
energy p s 300 GeV extends the accessible **kinematic** region in x and Q 2 by two orders of
experiments H1 and ZEUS allow an extension of the **kinematic** coverage towards very large values in the
are the most precise data obtained by H1 in this **kinematic** region so far. The full line in Fig. 1 depicts
www-h1.desy.de/psfiles/proceedings/llouise-98fl.ps

CiteSeer Find: |spring | Documents | Citations |

Searching for **PHRASE spring variable pitch side load**.
Restrict to: Header Title Order by: Expected citations Hubs Usage Date Try: Google (CiteSeer)
Google (Web) Yahoo! MSN CSB DBLP
No documents match Boolean query. Trying non-Boolean relevance query.
500 documents found. **Order: relevance to query.**

Meaningless Terms in Rewriting - Richard Kennaway (1996) (Correct) (12 citations)
Terms in Rewriting "ALP'96, LNCS 1139, **Spring**er-Verlag, Berlin, 1996, 254-268. Meaningless
from outside" by matching it against a proper non-**variable** subterm of a left-hand **side** (e.g. when one
a proper non-**variable** subterm of a left-hand **side** (e.g. when one extracts from a term Cons(t t 0
ftp.cs.vu.nl/pub/papers/theory/IR-418.ps.Z

Green's Function Methods in Heavy Ion Shielding - John Wilson (1993) (Correct)
dE 0 e S j (E 0 22) and defining new field **variables** as /j (x r j)e S j (E)OE j (x E)23) G
element through the sphere center to the opposite **side** of the sphere defines a cylinder through which
techreports.larc.nasa.gov/pub/techreports/larc/93/tp3311.ps.Z

A Neural Network Autoassociator for Induction.. - Petsche.. (1996) (Correct) (7 citations)
the motor be tested only when it is driving a known **load**. Neither the human motor expert nor the existing
Must Adapt To Or Factor Out The Effect Of Changing **Loads** On The Motor. Finally Since The Samms li Would
that, for a single motor driving a variety of **loads**, it is possible to distinguish Table 1: **Loads**
scr.siemens.com/pub/learning/Papers/petsche/motor-failure-prediction.ps

Scalability in Distributed Multimedia Systems - Korkea-Aho (1995) (Correct)
In The World Wide Web 60 Whose Replicas Are **Spread** Throughout The Internet. Furthermore The
is one which continues to work even though some **variables** in the system vary, usually to a great extent.
the client then waits for a reply. On the server **side**, the request header is parsed, the task dened by
www.hut.fi/~mkorkeaa/thesis.ps.gz

Evaluating High Level Parallel Programming Support .. - Chien, Dolby.. (Correct) (3 citations)
New Haven, Connecticut, 1992. YALEU/DCS/RR-915, **Spring**er-Verlag Lecture Notes in Computer Science,
remaining fundamental concerns -data locality and **load** balance -much easier. These two require
to express application specific data locality and **load** balance, the orthogonal framework for
www-csag.ucsd.edu/papers/csag/external/iscope.ps

Synchronization of Multimedia Streams in Distributed.. - Stoica, Abdel-Wahab, Maly (1997) (Correct)
(1 citation)
processing, buffering)may introduce a **variable** skew between the times when the frames actually
best-effort system. First, we show how the **load** variation at the source may lead to an erroneous
that is robust in the presence of network and CPU **load** variations, and extend it for the general case of
www.cs.odu.edu/~techrep/techreports/TR_97_19.ps.Z

Reasoning about Action in First-Order Logic - Elkan (1992) (Correct) (29 citations)
from an example. In Working Notes of the AAAI **Spring** Symposium on Logical Formalizations of
an instance of any of its left- or right-hand-**side** conjuncts becomes true or false. If anything,
objects, a person Fred and a gun, three fluents, **load**ed, alive, and dead, and three actions, **load**, wait,
www-cse.ucsd.edu/~elkan/papers/cscsi92.ps

Scalable Consistency Protocols for Distributed Services - Ahamad, Kordale (1999) (Correct) (3 citations)
hierarchy of local area and wide area networks and **spread** across several metropolitan areas. This study
and write-fault events are shown at the client **side**. When a client experiences an access miss or fault
based consistency protocol along the system **load** and geographic distribution dimensions of scale.
www.cc.gatech.edu/fac/Mustaque.Ahamad/pubs/scalable.ps

The Performance Potential of Data Dependence Speculation Collapsing - Sazeides (1996) (Correct)
(5 citations)
demonstrate stride behavior. ffl On the positive **side**, the percentage of incorrect predictions is very
is used to eliminate address generation-**load** dependences. This is enabled by address prediction
This is enabled by address prediction that permits **load** instructions to proceed speculatively without
einstein.et.tudelft.nl/~stamatis/pubs/confps/micro29.96.ps

On Adaptive Non-Linear Shell Analysis - Mathisen, Tiller, Okstad.. (1998)   (Correct)
be obtained by smoothing of the FE quantities. The **SPR**-method by Zienkiewicz and Zhu 24 has become the
that directly follow the transfer of solution **variables** after a mesh refinement, where we do not know
material tensor. The second term in the right hand **side** of (8) represents the geometric stiffness and
www.sima.sintef.no/~kmo/reports/WCCM_IVb.ps.gz

Autoscheduling in a Distributed Shared-Memory Environment - Jos'e Moreira (1994)   (Correct)   (8 citations)
of N instances of this HTG. An HTG may have local **variables**, which can be accessed by any task in the HTG,
in the physical partition, achieving better **load** balance than purely static schemes. We present the
support our main thesis: With minimal control, the **load** balancing and resource utilization advantages
ftp.csrd.uiuc.edu/pub/CSRD_Reports/reports/1373.ps.gz

The Comfort Automatic Tuning Project - Weikum, al. (1994)   (Correct)   (14 citations)
length, that is, the same number of lock requests **spre**ad evenly over the transaction execution. Under
times are usually not regular, but are random **variables** that are generated by some stochastic process.
by bookkeeping costs as one could think, but, as a "**side** effect"K=2 also minimizes the storage overhead
paris.cs.uni-sb.de/public_html/papers/infosys2.ps.Z

On Partitioning Dynamic Adaptive Grid Hierarchies - Manish Parashar (1996)   (Correct)   (22 citations)
Dec. 1995. 6] Hans Sagan, Space-Filling Curves, **Springer**-Verlag, 1994. 7] Manish Parashar and James C.
computationally efficient runtime partitioning and **load**-balancing scheme for the Distributed Adaptive Grid
Further, it enables dynamic re-partitioning and **load**balancing of the adaptive grid hierarchy to be
www.cs.utexas.edu/users/dagh/./Papers/hicss.ps

Load Balance Properties of Distributed Data Layouts for.. - Milind Buddhikot (1995)   (Correct)
for publication in the Special Issue of ACM/**Springer** Multimedia Systems Journal. 10] Chang, Ed,
length in terms of playout duration. In case of a **Variable** Bit Rate (vbr) video such as mpeg video, a chunk
Load Balance Properties of Distributed Data Layouts
www.cs.wustl.edu/cs/techreports/1995/wucs-95-32.ps.Z

Practical Algorithms for Selection on Coarse-Grained.. - Ibraheem Al-Furiah   (Correct)
Algorithms and Computation, Beijing, China, 1994, **Springer**-Verlag Lecture Notes in CS 834, 92-100. 18] S.
elements (I j) 1 and I j) 2)lie on one **side** of the element with rank k j) thus causing an
selection. We also consider several algorithms for **load** balancing needed to keep a balanced distribution
ftp.npac.syr.edu/pub/docs/sccs/papers/ps/0700/sccs-0743.ps.Z

Access Order and Memory-Conscious Cache Utilization - McKee, Wulf (1995)   (Correct)   (2 citations)
782 (PLSA, Zurich, Switzerland, March 1994)**Springer** Verlag, 1994. 26] McMahon, F.H.The
schemes: naive ordering, or using caching **loads** to access vector elements in the natural order of
computation streaming elements using non-caching **loads**, and then copying them to cache
ftp.cs.virginia.edu/pub/techreports/CS-94-10.ps.Z

Pthreads for Dynamic Parallelism - Narlikar, Blelloch (1998)   (Correct)
1993. Intel Corp. and the Portland Group, Inc.**Springer**-Verlag. 14] Rohit Chandra, Anoop Gupta, and
functionality, which includes locks and condition **variables**. We modify an existing native Pthreads library
onto the processors and effectively balances the **load**. However, unless the threads scheduler is designed
reports-archive.adm.cs.cmu.edu/anon/1998/CMU-CS-98-114.ps

Scheduling Fine-Grained Distributed Simulations in Wide-Area.. - Weissman, Jiang   (Correct)
means that machine resources may suffer dynamic **load** fluctuations or may be added or removed during the
In addition to chunk size, there is the issue of **load** balancing vs. **load** sharing. Task synchronous
size, there is the issue of **load** balancing vs. **load** sharing. Task synchronous applications require a
ringer.cs.utsa.edu/faculty/jon/./papers/gsim.ps.Z

A Highly Available, Scalable ITV System - Nelson, Linton, Owicki (1995)   (Correct)   (4 citations)
distributed objects architecture, similar to **Spring**[1]We have extended a standard name service
into client programs, read from environment **variables**, or determined in some idiosyncratic way. It
interface file to generate the client and server-**side** stubs. 3. Run a tool that creates a skeleton
www.star-lab.com/owicki/papers/itv.ps

Definite Descriptions and the Dynamics of Mental States - Poesio (1993)   (Correct)   (1 citation)
in task-oriented dialogues. In Working Notes AAAI **Spring** Symposium on Reasoning about Mental States:
2 In (2)as in the rest of the paper, I use **variables** with an `e' suffix like e or ce to denote
and send that off to Corning 13.5 now while we're **load**ing that boxcar with oranges at Corning, 13.6 we're
ftp.cogsci.ed.ac.uk/pub/poesio/AAAI_spring_93.ps.gz

IEEE Xplore®
RELEASE 2.1

Welcome United States Patent and Trademark Office

☐ Search Results

BROWSE   SEARCH   IEEE XPLORE GUIDE

Results for "(parallel kinematic<in>metadata)"
Your search matched **26** of **1227909** documents.
A maximum of **100** results are displayed, **25** to a page, sorted by **Relevance** in **Descending** order.

☑ e-mail

» **Search Options**

View Session History

New Search

» **Key**

IEEE JNL	IEEE Journal or Magazine
IEE JNL	IEE Journal or Magazine
IEEE CNF	IEEE Conference Proceeding
IEE CNF	IEE Conference Proceeding
IEEE STD	IEEE Standard

Modify Search

(parallel kinematic<in>metadata)   »

☐ Check to search only within this results set

Display Format: ⦿ Citation ○ Citation & Abstract

Select   **Article Information**

☐   1. **Kinematic calibration on a parallel kinematic machine tool of the Stewart circular tests**
Ibaraki, S.; Yokawa, T.; Kakino, Y.; Nakagawa, M.; Matsushita, T.;
American Control Conference, 2004. Proceedings of the 2004
Volume 2, 30 June-2 July 2004 Page(s):1394 - 1399 vol.2

AbstractPlus | Full Text: PDF(756 KB)   **IEEE CNF**

☐   2. **Stiffness estimation of a tripod-based parallel kinematic machine**
Tian Huang; Xingyu Zhao; Whitehouse, D.J.;
Robotics and Automation, IEEE Transactions on
Volume 18, Issue 1, Feb. 2002 Page(s):50 - 58
Digital Object Identifier 10.1109/70.988974

AbstractPlus | References | Full Text: PDF(377 KB)   **IEEE JNL**

☐   3. **A new method for tuning PID parameters of a 3 DoF reconfigurable parall machine**
Yang Zhiyong; Huang Tian;
Robotics and Automation, 2004. Proceedings. ICRA '04. 2004 IEEE Internatior
Volume 3, Apr 26-May 1, 2004 Page(s):2249 - 2254 Vol.3
Digital Object Identifier 10.1109/ROBOT.2004.1307396

AbstractPlus | Full Text: PDF(448 KB)   **IEEE CNF**

☐   4. **Analysis and simplification of the rigid body dynamic model for a 6-UPS kinematic machine under the uniform motion condition**
Zhang Lixin; Wang Jinsong; Wang Liping;
Robotics, Intelligent Systems and Signal Processing, 2003. Proceedings. 2003
International Conference on
Volume 2, 8-13 Oct. 2003 Page(s):980 - 985 vol.2
Digital Object Identifier 10.1109/RISSP.2003.1285721

AbstractPlus | Full Text: PDF(572 KB)   **IEEE CNF**

☐   5. **Stiffness analysis of a Stewart platform-based parallel kinematic machine**
Yu-Wen Li; Jin-Song Wang; Li-Ping Wang;
Robotics and Automation, 2002. Proceedings. ICRA '02. IEEE International Co
Volume 4, 11-15 May 2002 Page(s):3672 - 3677 vol.4
Digital Object Identifier 10.1109/ROBOT.2002.1014280

AbstractPlus | Full Text: PDF(551 KB)   **IEEE CNF**

☐   6.
Stiffness estimation of a tripod-based parallel kinematic machine
Huang, T.; Mei, M.P.; Zhao, X.Y.; Zhou, L.H.; Zhang, D.W.; Zeng, Z.P.; Whiteh
Robotics and Automation, 2001. Proceedings 2001 ICRA. IEEE International C

Volume 4, 2001 Page(s):3280 - 3285 vol.4
Digital Object Identifier 10.1109/ROBOT.2001.933124

AbstractPlus | Full Text: PDF(452 KB)   IEEE CNF

7. **Parallel kinematic machines for an application in shoes manufacturing: tl design to the first experimental campaign**
Molinari-Tosatti, L.; Fassi, I.;
Intelligent Robots and Systems, 2001. Proceedings. 2001 IEEE/RSJ Internatio
on
Volume 1, 29 Oct.-3 Nov. 2001 Page(s):433 - 438 vol.1
Digital Object Identifier 10.1109/IROS.2001.973395

AbstractPlus | Full Text: PDF(559 KB)   IEEE CNF

8. **Real-time force optimization in parallel kinematic chains under inequality**
Nahon, M.A.; Angeles, J.;
Robotics and Automation, IEEE Transactions on
Volume 8, Issue 4, Aug. 1992 Page(s):439 - 450
Digital Object Identifier 10.1109/70.149943

AbstractPlus | Full Text: PDF(940 KB)   IEEE JNL

9. **Kinematic analysis of a Stewart platform manipulator**
Liu, K.; Fitzgerald, J.M.; Lewis, F.L.;
Industrial Electronics, IEEE Transactions on
Volume 40, Issue 2, April 1993 Page(s):282 - 293
Digital Object Identifier 10.1109/41.222651

AbstractPlus | Full Text: PDF(872 KB)   IEEE JNL

10. **Kinematic modeling of four-point walking patterns in paraplegic subjects**
Zefran, M.; Bajd, T.; Kralj, A.;
Systems, Man and Cybernetics, Part A, IEEE Transactions on
Volume 26, Issue 6, Nov. 1996 Page(s):760 - 770
Digital Object Identifier 10.1109/3468.541336

AbstractPlus | References | Full Text: PDF(1396 KB)   IEEE JNL

11. **Optimized binary modular reconfigurable robotic devices**
Hafez, M.; Lichter, M.D.; Dubowsky, S.;
Mechatronics, IEEE/ASME Transactions on
Volume 8, Issue 1, March 2003 Page(s):18 - 25
Digital Object Identifier 10.1109/TMECH.2003.809156

AbstractPlus | References | Full Text: PDF(1175 KB)   IEEE JNL

12. **Type synthesis of 3T1R 4-DOF parallel manipulators based on screw thei**
Xianwen Kong; Gosselin, C.M.;
Robotics and Automation, IEEE Transactions on
Volume 20, Issue 2, April 2004 Page(s):181 - 190
Digital Object Identifier 10.1109/TRA.2003.820853

AbstractPlus | References | Full Text: PDF(400 KB)   IEEE JNL

13. **Universal communication architecture for high-dynamic robot systems u**
Kohn, N.; Varchmin, J.-U.; Steiner, J.; Goltz, U.;
Control, Automation, Robotics and Vision Conference, 2004. ICARCV 2004 8tl
Volume 1, 6-9 Dec. 2004 Page(s):205 - 210 Vol. 1
Digital Object Identifier 10.1109/ICARCV.2004.1468823

AbstractPlus | Full Text: PDF(344 KB)   IEEE CNF

14. **Research on combined framework and measurement design of parallel k machines (PKM) digital prototyping**
Fan Zhang; Zhe Yin; Liwen Guan; Liping Wang;
Systems, Man and Cybernetics, 2004 IEEE International Conference on
Volume 5, 10-13 Oct. 2004 Page(s):4389 - 4393 vol.5
Digital Object Identifier 10.1109/ICSMC.2004.1401222

AbstractPlus | Full Text: PDF(652 KB)   IEEE CNF

15. **A high performance 6-DOF haptic Cobot**
Faulring, E.L.; Colgate, J.E.; Peshkin, M.A.;
Robotics and Automation, 2004. Proceedings. ICRA '04. 2004 IEEE Internatioı
Volume 2, Apr 26-May 1, 2004 Page(s):1980 - 1985 Vol.2
Digital Object Identifier 10.1109/ROBOT.2004.1308114

AbstractPlus | Full Text: PDF(576 KB)   IEEE CNF

16. **The measurement of kinematic accuracy for various configurations of pa manipulators**
Tiemin Li; Peiqing Ye;
Systems, Man and Cybernetics, 2003. IEEE International Conference on
Volume 2, 5-8 Oct. 2003 Page(s):1122 - 1129 vol.2

AbstractPlus | Full Text: PDF(555 KB)   IEEE CNF

17. **Identifiability of geometric parameters of 6-DOF PKM systems using a mi pose error data**
Tian Huang; Jinsong Wang; Chetwynd, D.G.; Whitehouse, D.J.;
Robotics and Automation, 2003. Proceedings. ICRA '03. IEEE International Cc
Volume 2, 14-19 Sept. 2003 Page(s):1863 - 1868 vol.2
Digital Object Identifier 10.1109/ROBOT.2003.1241866

AbstractPlus | Full Text: PDF(403 KB)   IEEE CNF

18. **Design of a redundantly actuated leg mechanism**
Byung Rok, So.; Byung-Ju, Yi.; Wheekuk, Kim.; Sang-Rok, Oh.; Jongil, Park.;
Robotics and Automation, 2003. Proceedings. ICRA '03. IEEE International Cc
Volume 3, 14-19 Sept. 2003 Page(s):4348 - 4353 vol.3
Digital Object Identifier 10.1109/ROBOT.2003.1242273

AbstractPlus | Full Text: PDF(396 KB)   IEEE CNF

19. **Twice: a tilting angle amplification system for parallel robots**
Krut, S.; Company, O.; Marquet, F.; Pierrot, F.;
Robotics and Automation, 2002. Proceedings. ICRA '02. IEEE International Cc
Volume 4, 11-15 May 2002 Page(s):4108 - 4113 vol.4
Digital Object Identifier 10.1109/ROBOT.2002.1014388

AbstractPlus | Full Text: PDF(542 KB)   IEEE CNF

20. **Kinematically dual manipulators**
Bruyninckx, H.;
Robotics and Automation, 1999. Proceedings. 1999 IEEE International Confer
Volume 2, 10-15 May 1999 Page(s):1194 - 1199 vol.2
Digital Object Identifier 10.1109/ROBOT.1999.772524

AbstractPlus | Full Text: PDF(420 KB)   IEEE CNF

21. **Parallel kinematics and PC-based control system for machine tools**
Pritschow, G.; Tran, T.L.;
Decision and Control, 1998. Proceedings of the 37th IEEE Conference on
Volume 3, 16-18 Dec. 1998 Page(s):2605 - 2610 vol.3
Digital Object Identifier 10.1109/CDC.1998.757844

AbstractPlus | Full Text: PDF(468 KB)   IEEE CNF

22. **Real-time force optimization in parallel kinematic chains under inequality**
Nahon, M.; Angeles, J.;
Robotics and Automation, 1991. Proceedings., 1991 IEEE International Confeı
9-11 April 1991 Page(s):2198 - 2203 vol.3
Digital Object Identifier 10.1109/ROBOT.1991.131956

AbstractPlus | Full Text: PDF(552 KB)   IEEE CNF

23. **Conceptual design and dimensional synthesis for a 3-DOF module of the novel 5-DOF reconfigurable hybrid robot**
Huang, T.; Li, M.; Zhao, X.M.; Mei, J.P.; Chetwynd, D.G.; Hu, S.J.;
Robotics, IEEE Transactions on [see also Robotics and Automation, IEEE Tra

Volume 21, Issue 3, June 2005 Page(s):449 - 456
Digital Object Identifier 10.1109/TRO.2004.840908

AbstractPlus | Full Text: PDF(640 KB)   IEEE JNL

24. **Measurement of the axial forces and rotation torques in case of hexapod tools**
Popescu, D.;
Advanced Motion Control, 2002. 7th International Workshop on
3-5 July 2002 Page(s):275 - 278
Digital Object Identifier 10.1109/AMC.2002.1026930

AbstractPlus | Full Text: PDF(401 KB)   IEEE CNF

25. **Micropositioners for microscopy applications based on the stick-slip effe**
Bergander, A.; Breguet, J.-M.; Schmitt, C.; Clavel, R.;
Micromechatronics and Human Science, 2000. MHS 2000. Proceedings of 20(
Symposium on
22-25 Oct. 2000 Page(s):213 - 216
Digital Object Identifier 10.1109/MHS.2000.903315

AbstractPlus | Full Text: PDF(464 KB)   IEEE CNF

Help   Contact Us   Privacy & :